

CERTIFICATE

No. U6 105828 0002 Rev. 00

Holder of Certificate: **Interlight Enjoy Innovation BV**
Smalriemseweg 6
4112 NC Beusichem
THE NETHERLANDS

Certification Mark:




Product: **Power supplies
(LED Driver)**

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142225036701B

Date, 2023-08-25



(Taylor Yao)

CERTIFICATE

No. U6 105828 0002 Rev. 00

Model(s): IL-X2D15-1-10; IL-X2D40-1-10;
IL-D53DALI2; IL-D29DALI2;
IL-DC9D; IL-DC10D;
IL-DC13D; IL-DC14D

Brand Name: INTERLIGHT



Parameters:

Rated Input Voltage: See below table for details

Rated Frequency: 50/60Hz

Rated Input Current: See below table for details

Rated Output: See below table for details

Protection against Electric Shock: Class II; SELV

Degree of Protection: IP20

Method of Installation: Independent

Type of Output: Constant current type

ta: See below table for details

tc: See below table for details

Tested according to: EN 61347-2-13:2014/A1:2017
EN 61347-1:2015/A1:2021
EN IEC 62384:2020

Production Facility(ies): 097674

CERTIFICATE

No. U6 105828 0002 Rev. 00

Model	Rated Input Voltage (VAC)	Rated Input Current (A Max.)	Output Voltage (VDC)	I _{rated} (mA)	U _{out} (VDC)	P _{rated} (W)	Value of ta; tc (°C)						
IL-X2D15-1-10	110-277	0.2	14-42	160	49	6.8	50; 80						
				180		7.6							
				220		9.3							
				280		11.8							
				320		13.5							
				350		14.7							
IL-X2D40-1-10	110-277	0.52	14-42	400	49	16.8	50; 90						
				500		21.0							
				600		25.2							
				700		29.4							
				800		33.6							
				900		37.8							
			14-38	1000		38.0							
				1100		41.8							
				IL-D53DALI2		220-240		0.3	14-42	50	650	27.3	45; 90
											700	29.4	
750	31.5												
800	33.6												
850	35.7												
900	37.8												
950	39.9												
1000	42												
1050	44.1												
1100	46.2												
IL-D29DALI2	220-240	0.18	14-42	50	250	10.5	45; 90						
					300	12.6							
					350	14.7							
					400	16.8							
					450	18.9							
					500	21							
					550	23.1							
					600	25.2							
					IL-DC9D	220-240		0.06	30-38	56	120	4.6	50; 75
140	5.3												
160	6.1												
180	6.8												
200	7.6												
220	8.4												



Product Service

CERTIFICATE

No. U6 105828 0002 Rev. 00

IL-DC10D	220-240	0.065	14-21	250	36	5.3	50; 75
				300		6.3	
				350		7.4	
				400		8.4	
			14-20	450		9.0	
			14-18	500		9.0	
IL-DC13D	220-240	0.085	30-38	250	56	9.5	50; 80
				280		10.6	
				300		11.4	
				320		12.2	
				350		13.3	
IL-DC14D	220-240	0.09	14-21	500	36	10.5	50; 80
				550		11.5	
				600		12.6	
				650		13.6	
				700		14.7	
			14-18	750		13.5	

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFIKAT ◆ CERTIFICAT